

## Republic of the Philippines

## Department of Education

## REGION XI SCHOOLS DIVISION OF DAVAO ORIENTAL

## **REQUEST FOR QUOTATION**

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the last page, stating the

shortest time of delivery and submit your quotation duly signed by your representative not later than September 29, 2025 in the

Company Name:

Address:

September 23, 2025

Quotation No.: 2025-09-0017-1

Date:

return env	elope attacl	hed herewith.	(	CHAISTAN N. S	ANGO	
2. 3. pr 4. 5.	<ol> <li>All entries must be typewritten.</li> <li>Delivery period within calendar days upon receipt of the Purchase Order.</li> <li>Warranty shall be for a period of six (6) months for suppliers and materials, one (1) year for Equipment, from date of acceptance by the procuring entity.</li> <li>Price validity shall be for a period of 45 calendar days.</li> <li>PhilGEPS Registration Certificate shall be attached upon submission of the Quotation.</li> <li>Bidders shall submit Original Brochures showing certificates of the product being offered.</li> </ol>					
Stock/ Property	Unit	Item Description	Qty	Unit Price	Total Cost (VAT Inclusive)	
		Lot 1				
		Brand and Model: Delivery Period: Warranty: Price Validity:				
	After havir	ng carefully read and accepted your General Conditions, I	/We quote you on the	e item at prices	noted above.	
Page 1 of	3	Canvasser/s	Printed P	Vame / Signatu Bidder	re	

Stock/ Property	Unit	Item Description	Qty	Unit Price	Total Cost (VAT Inclusive)
1	days	Total Station with complete accessories (tripod, range pole, prism, etc.) Description: Angle Measurement:  • Measurement Method: Absolute Encoding  • Minimum Readout: 1"/5"/10" (0.3 mgon / 1.5 mgon / 3 mgon)  • Accuracy: 2" Distance Measurement Prism Mode  • Single Prism: 3000 m (19,685 ft.) under good condition  • Three Prisms: 6000 m (19,685 ft.) under good condition  • Reflective Sheet: 800 m (2,624 ft.)  • Accuracy: 2 mm + 2 ppm  • Measuring Time (Fine / Quick / Tracking): 1.5s / 1s / 0.5s Distance Measurement Nor-Prism Mode:  • Reflectoriess Range: 400 m (1,312 ft.)  • Single Prism: > 7500 m (24,606 ft.)  • Accuracy: 3 mm + 2 ppm  • Measuring Time: 1.5s Telescope:  • Magnification: 30 X  • Field of View: 1"30" (2.7 m at 100 m)  • Minimum Focusing Distance: 1.2 m  • Reticle: Illuminated Compensator:  • System: Dual-axis liquid tilt sensor  • Working Range: ±3"  • Setting Accuracy: 6" Communication:  • Interface: Standard R5232, Micro USB  • Internal Memory: Approx. 20,000 Points  Data Format: ASCII Operation:  • Operating System: Real-time Operating System  Display: High-resolution backlight, black and white display with contrast adjustment  Craphics: 192 x 96 pixels / Character: 6 lines x 25 characters  • Keyboard: 2-sided Alphanumeric backlit crystal keyboard Laser Plummet:  • Type: Laser point, 4 brightness levels adjustment  • Centering Accuracy: 1 mm at 1.5m instrument height Power Supply:  • Battery Type: Rechargeable Li-ion battery  • Voltage/Capacity: BT10: 7.4 V (DC) / 3000 mAh  • Operating Time: Optimal 16 hours (Continuous angle measurement every 30 seconds) / 10 hours (typical)  • Measuring Times: Approx. 12000 times	20		
	After beer	Brand and Model:  Delivery Period:  Warranty:  Price Validity:			
,	Atter havir	ng carefully read and accepted your General Conditions, I/We quot	e you on the	e item at prices	noted above.
Page 2 of 3		Canvasser/s		lame / Signatur Bidder	e

Stock/ Property	Unit	Item Description	Qty	Unit Price	Total Cost (VAT Inclusive)
2	days	Global Navigation Satellite System – Real-Time Kinematic (GNSS-RTK) with complete accessories (controller, tripod, etc.) Specifications:  1000 channels  IP 68 (minimum)  GNSS Board: must be originally designed, made, and manufactured by the same brand offered  Satellite Tracking: GPS, GLONASS, BEIDOU, GALILEO, QZSS, SBAS  RAM: 512MB  Network Protocols: Ntrip Client, Ntrip Server  Accuracy: Minimum  Lithium Battery: 6400mAh x 2 (must be detachable) with LED light indicator  Cellular: 4G LTE/TD-SCDMA/WCDMA/GPRS/GSM  WiFi: 802.11b/g  Bluetooth: 4.1 (must reach up to 40 m from receiver to controller)  USB: USB 2.0 x 1  Serial Port: RS-232 x 1  Internal Radio-Power: 2W (must reach at least 10 km)  Frequency: 410 MHz – 470 MHz  Weight: approximately 1.1kg (without battery)  Operating Temperature: -40° to +70°  Storage Temperature: -55°C to +85°C	20		
		<ul> <li>Relative Humidity: 100% not condensed</li> <li>Pole-drop onto concrete: 2m</li> </ul>			
ABC:	160,00	0.00			
ABC:		Brand and Model: Delivery Period: Warranty: Price Validity:  ng carefully read and accepted your General Conditions, I/We que	ote you on th	e item at prices	s noted above.
		Brand and Model:  Delivery Period:  Warranty: Price Validity:	ote you on th	e item at prices	s noted above.